



## eToAccess - VDSL2 LAN Extender 100 Series

### eTo inc.,

15-3 Dasi Rd Dacun Changhua  
51543 Taiwan, R. O. C.  
Tel: 886-4-852-9443  
Fax: 886-4-853-6475  
ebsite: [www.etotek.com.tw](http://www.etotek.com.tw)

### VDSL2 LAN Extender 100 Series Description

eTo 100 VDSL2 LAN Extender is a Long Reach Ethernet Extender with one Ethernet port(RJ-45 connector) and one VDSL port(RJ-45 connector) it is a bridge mode modem,well accommodation VDSL2 (Very-high-data-rate Digital Subscribe Loop) technology to extend Ethernet service over single-pair phone line. Supporting both symmetric and asymmetric transmission, it can reach up to 100/75 Mbps bandwidth (line rate) within 300M or 10/10 Mbps (line rate) for 1 Km long range connections.By providing ultra-high speed, eTo VDSL2 100 LAN Extender makes your telephone line achieve its best performance than before. It has the advantage of minimum installation time (simply as plug-n-play) and minimum expense by allowing video streaming and data to share the same telephone pair without interference.

eTo 100 VDSL2 LAN Extender delivers everything needed to quickly deploy a high-speed IP-based network for providing high-speed Internet access,video-on demand services and voice services. The resulting compact, cost-effective form factor offers Systems Integrators, small business owners on attractive Long Reach Ethernet solution.



VDSL2 Bridge

### VDSL2 LAN Extender 100 Series Feature

- Cost effective bridge function to connect two Ethernet LAN
- Support flow control on Fast Ethernet port via PAUSE frame or Back Pressure
- IEEE 802.1Q VLAN tag transparent
- Easy installation via simple plug-and-play
- Selectable CPE and CO mode via DIP switch:  
Two working modes are built in the same unit,which keep the flexibility of installation and easy provision of service but lower inventory of service provider.
- Selectable fast and interleaved mode:  
Fast mode guarantees a minimum end to end latency less than 1 ms. Interleaved mode provides impulse noises protection for any impulse noise with a duration less than 250 us, Interleaved mode has a maximum end to end latency of 10 m sec. Interleaved mode is the default mode.
- Selectable target band plan:  
Symmetric:Support the band plan G.997 and provide the symmetric transmission on both down stream and upstream.  
Asymmetric:Provides highest line rate in short range in asymmetric mode.
- Selectable target SNR margin:  
User has the ability to select fixed SNR margin(9 dB) or fixed target data rate. When fixed SNR margin is selected, the systems will maintain the SNR margin at 9 dB across all usable loop length. When fixed target data rate is selected, the system will lock the data rate up to 50 Mbps/30 Mbps whenever the calculated SNR margin is higher than 9 dB. This gives best system stability and is the default mode.



# eToAccess - VDSL2 LAN Extender 100 Series

## eTo inc.,

5F-7, NO.161, Gongyi Rd.,  
West District, Taichung City,  
403 Taiwan, R. O. C.

Tel: 886-4-2301-1686  
Fax: 886-4-2301-9627

Website: www.etotek.com.tw

### VDSL2 LAN Extender 100 Series Specification

#### 4-position DIP Switch

- Selectable CO or CPE mode
- Selectable fast or interleave mode (Impulse noise protection)
- Selectable Band plan (Symmetric or Asymmetric)
- Selectable target SNR margin (6dB or 9dB)

#### LAN Interface:

- RJ-45 connector
- Complying with IEEE 802.3/802.3u/802.3x
- 10/100 Base-T Auto-Negotiation, Auto-MDI/MDI-X.

#### LED:

- LAN:ACT/LNK, 10/100 Mbps, Half/Full Duplex
- VDSL:Power On/Off, CO/CPE, Idle/Trained/Link

#### VDSL Interface:

- RJ-45 connector
- DMT Encoding
- Complying with ITU-T G993.1/993.2/G.997.1
- On-board surge protection

#### Power supply:

- DC single 12 Volt over 3.5mm DC jack; 4.2 Watt maximum.

**Dimension: 73.4mm x 96.2mm x 22.8mm**

**Temperature: 0~45 degree C**

**Humidity: 0%~95%RH(non-condensing)**

**Emission: EN55022 Class B, EN 55024, IEC 61000-4, CE mark**

**Safety: EN 60950, CE mark**

#### Mini Rack 800

Mini Rack 800 is a 2U 10-inch 8-slot mini-size rack with one Internal AC or DC Power as the concentrator of compact size media converters or LAN Extender. Up to eight units of eTo 100 VDSL2 LAN Extender can be powered by Mini Rack 800 without the requirement of external AC power adapter. Mini Rack 800 can be used as a table top unit or installed into a 19-inch rack side by side.

#### Key Features

- 2U height, 8-Slots for eTo 100 VDSL2 LAN Extender
- Suitable for 19-inch by keeping 2 units abreast with each other
- One cooling fan per Rack
- Plug & Play Operation
- With fixed AC or DC Power Install

#### Specifications

- Slot Capacity: 8 Slide-in units
- Dimension and Weight  
Size: 251.6 x 196 x 88.6 mm (W x D x H)  
Shipping Weight: 1.74 Kg
- Emission/Safety: FCC Part 15 Class A, CE Mark
- Power  
AC Power Input: 90~250VAC  
DC 24 Power Input: 18~36VDC  
DC 48 Power Input: 36~72VDC
- Power Consumption: 45W max
- Operation & Storage Temperature  
Operating Temperature: 0~50 degree C  
Storage Temperature: -20~60 degree C  
Humidity: 5 to 90%

### VDSL2 LAN Extender Ordering Information

- 100 VDSL2 LAN Extender
- 800-AC 8 slots FMC Rack with Internal AC 100~240V
- 800-DC24 8 slots FMC Rack with Internal DC 24V
- 800-DC48 8 slots FMC Rack with Internal DC 48V