



## eToETH- VO308 SIP IP Phone

### eTo inc.,

5F-7, NO.161,Gongyi Rd.,  
West District ,Taichung City,  
403 Taiwan, R. O. C.

Tel: 886-4-2301-1686

Fax: 886-4-2301-9627

Website: www.etotek.com.tw

### VO308 Series SIP IP Phone benefits

The eToETH VO308 Series are next generation IP Phones that provide a simple, cost-saving solution for VOIP and telecommunication needs. The VO308 series follows RFC-3261 SIP protocol ensuring compatibility with most exiting VOIP service and products. The series offers versions with combinations of speakerphone,FXO port and PoE to meet user requirements. All models have a built-in LCD display and WEB management, it is also incredible easy to use! State-of-Art DSP technology( Digital Signal Processing) delivers outstanding voice quality comparable to that of the PSTN. Combine this with a rich telephone feature set such as call forward/transfer , speed dial , 3 way call ,Multiple SIP account and more ,makes the VO308 SIP IP Phone series the best choice.



VO308

### Key Feature

- 3 Way Call : Use as Conference call
- 3 Account Numbers : This Phone can register 3 SIP accounts at the same time
- Call forward Function : All Forward / Busy Forward / No Answer
- Message Light : The Phone have message light , but need to match with IP PBX
- Insert dials : During the calling , you can hear the insert dial sound if have the other call coming

### Feature

- Conference call : 3-way call
- Speed dial function
- Call Waiting function
- 140 Phone Book Number
- Call forward : All forward / Busy Forward / No Answer Forward
- Block setting : All / By Time / Duration
- Adjust Ringer volume
- Four types Ringer tone can select
- Upgrade program by FTP/TFTP/HTTP mode
- Support G.711 / G.723.1 / G.726 / G.729A / G.729B / GSM / iLBC codec algorithm
- 64 entries each for imcoming call and dialed call
- support Auto Provision by FTP/TFTP/HTTP
- LCD display dial data , caller name , caller number and so on
- Adjustable volume for both handset and speaker
- Setting by HTTP web browser



## eToETH- VO308 SIP IP Phone

### eTo inc.,

5F-7, NO.161,Gongyi Rd.,  
West District ,Taichung City,  
403 Taiwan, R. O. C.

Tel: 886-4-2301-1686

Fax: 886-4-2301-9627

Website: www.etotek.com.tw

#### Feature

- VPN Support PPTP ( option)
- Support Asterisk Open Source IP PBX
- Support IP PBX
- Speed Dial : 10
- Dial Plan Setting
- Support Hotline Setting
- Support Alarm Setting

#### Hardware characteristics

- LAN interface : 10Mbps/100Mbps
- WAN interface : 10Mbps/100Mbps
- Power Supply : Input : 100-240V / 50/60/Hz , Output: DC9V/500mA  
US/Euro/UK/Australian style available
- Phone body color : White & Gray
- LCD size : 2 x 16
- Unit Dimension/Weight : 23 cm x 18.2 cm x 12.1 cm / 0.8Kg
- Box Dimension/Weight : 33.8cm x 20.7 cm x 7.4 cm / 1.4Kg
- Operatonal Temperature : 0 to 40 degree C
- Storage Temperature : -10 to 50 degree C
- Relative Humidity : 10 - 90 % non-conensing
- Compliance : FCC/ CE / LVD / EMC
- Function Keys : 26 function keys besides standard key 0-9 ,#, \*

#### Package

- VO-306 IP Phone
- Power Adapter
- Ethernet Cable
- User Manual ( CD )



Color Plan

